



KS SECURITY SOLUTIONS LTD

i3 DVR



Software Configuration	
Number of analog channels	10 or 16
Screen display	1, 4, 6, 9, 10, 13, or 16
Pre-alarm/Post-alarm recording	Yes
Emergency frame rate recording	Yes
Backup video format	AVI, BMP, or JPEG
Hardware Configuration	
Operating system	Win XP
Standard SATA storage size	1HD w/OS
Max. number of additional HDD	2
Operating devices (CPU, graphics, RAM)	PCI Express, 2GB RAM DDR 2 or 3
Analog video loop out (75 Ohm, dip switch controlled)	16
VGA resolution requirement	1024 x 768
Number of spot monitors	1
Number of RS485 ports (PTZ)	2 [Optional UIO8 = 1 (TCP/IP)]
Connectivity (LAN/WAN)	1 X 1Gb/sec
Resolution and Compression	
Type of Compression	MJPEG
Analog display speed NTSC/PAL	up to 480/400fps 1CIF
Client Applications	
Remote viewing	IE 6.0, Proprietary Software, & SRX-Pro Player, i3Display
Number of PACDM™ channels Serial/TCP/IP	Optional Max. 4 lanes serial
Physical Environment and Certifications	
Type of chassis	Steel Alloy
Physical dimensions (LxWxH)	17.125"x13.25"x5.75" (434.98mmx336.55mmx146.05mm)
Warranty	
Standard Warranty	1 yr parts & 1 yr labour